



Certificate number: 2106754

Date issued 23rd June 2021

Date expired 22nd June 2026 Original/Amendment Original

Kiwa UK Regulation 4 (KUKreg4) Approval

ATS3 – Without Production Surveillance

Issued by Kiwa Watertec (UK)

Evaluation Guideline: Kiwa UK – EG004
Reference Standards: Regulators Specification
Model Designations: see Appendix

Manufacturer: Fluidmaster GB.

Kiwa Watertec declares that legitimate confidence exists in the products specified in this certificate and supplied by the above organisation be relied on to comply with the above Evaluation Guideline and Standards, and can be marked with the KUKreg4mark.

The intended use of this certificate is for compliance with Regulation 4(1)a of the Water Supply (Water Fittings) Regulations 1999 England & Wales; 2009 Northern Ireland and 2014 Byelaws Scotland

This certificate has been issued in accordance with the Kiwa regulations for product certification

Signed on behalf of Kiwa Watertec

David Jay,
Business Unit Manager – Authorised Signatory
Kiwa Watertec

Kiwa Watertec
(A Trading Division of Kiwa Ltd)
26A Rassau Industrial Estate
Ebbw Vale
Gwent
NP23 5SD
United Kingdom
T +44 (0)1495 308185
uk.water@kiwa.com
www.kiwa.co.uk

Certificate issued to:
Fluidmaster GB
Twyford road
Rotherwas Industrial Estate
Hereford
HR2 6JR



UK Approval Certificate (page 2 of 2)

Appendix to Certificate 2106754

The following products are covered by this certificate -

PRODUCT DESCRIPTION Range of side or bottom entry BS1212-4 (2016) compact type float operated valves for WC flushing cisterns. The inlet incorporates a filter and restrictor. ATS3 – Without Production Surveillance.
MODEL(S) B610, B610-1/2B, B661-8.5.
SIZE: ½" BSP(M).
SCOPE: Manufacturer recommended maximum working pressure 10 Bar & maximum operating temperature: Cold water use only. Hygienic Purposes: Non-metallic materials suitable for continuous use with cold water only. Above ground use only.
MATERIALS Non-metallic materials assessed (BS6920) to point of discharge.
BACKFLOW PROTECTION NOTES When an independent inlet valve is used in conjunction with a cistern to form an independent flushing cistern or to form a WC suite, additional verification to validate backflow prevention arrangements is required. Please refer to the clarifications of the requirements of the Water Supply (Water Fittings) Regulations, Byelaws in Scotland, as they apply to Type AG and Type AUK1 air gaps in WC suites and the interim agreement.
MARKING Fluidmaster, 'Heart' logo and BS1212-4 on screw ring.
ADDITIONAL NOTES All water contact & exposed components satisfy opacity requirements.

Extra Notes