AQUARIUS A45

Polished with PEX Hose

AT03-013

The Aquarius range incorporate simple and modern design, with the latest electronic functionality.

Sensor operated for maximum hygiene and efficiency. 5 litres per minute integrated flow control. (Standard 5LPM, Other flow rates available)


Automatic purge function, Sensor range adjustment, Wave on/wave off function, Anti Vandal and Lock Out functions, Chlorination function.

Single mixed feed connection by PEX lined hose (15mm connection). External TMV required. Polished finish.

Requires a Station kit to operate. Station kits available in Single Station Battery or Mains Single Station, 2 Station or 3 Station for multiple connections. Refer to Station kit Data sheets.

AT03-013	Polished	A45 no touch tap
TECHNICAL DAT	A	
Type of tap		Aquarius A45
Material		316 Stainless Steel
Surface finish		Polished
Gross weight		1.1 kg
Type of operation		No Touch Sensor
Type of mounting		Deck mounted
Type of mixing		Additional TMV may be required
Automatic purge		Yes* - Default: OFF
		Options: 3, 6, 12, 24, 36 & 48 hours
Purge run time		Default 1 min*
		Options: OFF, 30 secs, 1, 2, 4 & 8 mins
Spout projection		118mm
Minimum flow pressure		1.00 bar (Lower pressure station kits available)
Volume flow rate at 3 bar		5LPM (Other flow rates available)
Adjustable run tin	ne	Yes* - Default: 2 secs
		Options: 2, 5, 10, 15, 20, 30 secs
Water connection		15mm PEX hose
Anti-Vandal function		Yes
Lock out function		Default OFF*
		Options: OFF, 4, 6, 8 & 10 operations
Chlorination function		Yes* - Default 2 mins
		Options: 1, 2, 3, 4, 5, 10, 20 & 30 mins
Battery or mains :	station kit	Single Battery: AT00-001
		Single Mains: AT00-002
		- Other options available. Contact DVS.
Working pressure		1-10 Bar (For Low / High pressure, Contact DVS.)
Max working temperature		60°C
Fixing		3⁄4" BSP
Fixing length		Up to 50mm with flange nut





Last Updated: 2015008-12, Dart Valley Systems ender Last Updated: 2015008-12, Dart