



Certificate number: 2410782 (1)

Issued 05/11/2024

Expires 05/11/2029

Kiwa Regulation 4 (KUKreg4) Certification

Evaluation Guideline – Kiwa UK – EG004 – Regulation 4(1)(a)

Model number(s) – see Appendix

KWC DVS.

Kiwa Watertec declares that legitimate confidence exists in the products specified in this certificate and supplied by the above organisation be relied upon to comply with the Kiwa Evaluation Guideline referred above.

Which verifies the requirements of:

Regulation 4(1)a of the Water Supply (Water Fittings) Regulations 1999 England & Wales: 2009 Northern Ireland and 2014 Byelaws Scotland.

This certificate has been issued in accordance with the Kiwa regulations for product certification.

Signed on behalf of Kiwa Watertec

David Jay, Business Unit Manager – Authorised Signatory
Kiwa Watertec

Publication of this certificate is allowed.

Products are intended to be used in the UK only. For other countries, other (National) requirements will apply.

See <https://www.kiwa.com/gb/en/about-kiwa/water-products/> or the QR code below to ensure that the certificate is still valid.

CERTIFICATE

Kiwa Watertec
(A Trading Division of Kiwa Ltd)
26A Rassau Industrial Estate
Ebbw Vale
Gwent
NP23 5SD
United Kingdom
T +44 (0)1495 308185
uk.water@kiwa.com
www.kiwa.co.uk

Certificate Issued to:

KWC DVS
Kemings Close
Long Road
Paignton
Devon
TQ4 7TW
United Kingdom



KUKreg4

Product Certificate

Appendix to Certificate number: 2410782

The following products belong to this certificate

| |
|---|
| <p>PRODUCT DESCRIPTION Range of urinal flushing systems with brass bodies, flow is controlled via a solenoid valve either battery or mains operated (see model) ATS3 – Without Production Surveillance.</p> |
| <p>MODEL(S) Flushmatic range: Battery operated UC01-001 - surface mounted in Grey UC01-003 - surface mounted in Grey UC01-004 - surface mounted in Stainless Steel UC01-005 - surface mounted in White UC01-006 - surface mounted in White UC01-007 - surface mounted with battery low indicator in Grey UC01-008 - surface mounted with battery low indicator in Stainless Steel UC01-009 - surface mounted with battery low indicator in White UC01-018 - downlighter kit for suspended ceilings in White Mains operated: UC01-014 - surface mounted in Grey UC01-015 - surface mounted in Grey UC01-016 - surface mounted in Stainless Steel UC01-017 - surface mounted in White UC01-024 - downlighter kit for suspended ceilings in White</p> |
| <p>SIZE: 15mm Compression.</p> |
| <p>SCOPE: Manufacturer recommended maximum working pressure 8.0 Bar & maximum operating cold water use only. Hygienic Purposes: Non-metallic materials suitable for continuous use up to 65°C.</p> |
| <p>MARKING DVS on front cover of housing.</p> |
| <p>MATERIALS Non-metallic materials assessed (BS6920) to point of discharge.</p> |
| <p>BACKFLOW PROTECTION NOTES N/A.</p> |
| <p>ADDITIONAL NOTES All water contact & exposed components satisfy opacity requirements.</p> |

Extra Notes