



AC01-001

Handheld programmer

The programmer will allow quick and easy adjustment of settings including; run-on-time, range, purge and more. Real time data can be uploaded from the programmer via the USB port to allow accurate monitoring of water efficiency.

Technical data

Operation

Via key pad and switch

Data processing

Data download directly into Microsoft Excel via USB interface

Charging

Via USB interface for minimum 8 hours

Time & date

Set via specific menu on controller

Programming options:

V2 tap menu

Run time, Range, Anti-vandal time, Automatic purge

Tap menu

Purge runtime

Run time, Sensor range, Wave On / Off operation

Shower menu

Anti vandal time

Run time, Sensor range, Wave On / Off operation,

Anti vandal time, Automatic purge Purge run time,

Urinal menu

Lock outs

Pre-Flush wait, Pre-Flush time, Main flush time,

Sensor range, Anti vandal time, Automatic purge,

Bath menu

Purge run time

Run time, Sensor range, Wave On / Off operation,

Anti vandal time, Automatic purge, Purge run time,

Auto flush valve menu

Lock outs

Range, User detect time, Dual detect time, Flush

time(s), Walk away time, Automatic purge,

Wave flush valve menu

Purge run time, Lock outs

Flush type, Flush time(s), Range, Automatic Purge,

Chlorinate menu

Purge run time, Lock outs

Chlorination time, Abort and reset