



Aquarius WM straight tap spout



AT02-022

Aquarius WM straight tap spout

The Aquarius range incorporate simple and modern design, with the latest electronic functionality. Sensor operated for maximum hygiene and efficiency, 5 litres per minute integrated flow control. (Standard 5LPM, Other flow rates available) Automatic purge function, Sensor range adjustment, Wave on/wave off function, Anti Vandal and Lock Out functions, Chlorination function. Single mixed feed connection by Copper tail (10mm). External TMV required. Brushed finish.

Technical data

Type of tap	Aquarius WM straight
Material	316 stainless steel
Surface finish	Brushed
Gross weight	1.3kg
Type of operation	No touch sensor
Type of mounting	Wall mounted
Type of mixing	Additional TMV may be required
Automatic purge	Yes* - default: off Options: 3, 6, 12, 24, 36 & 48 hours
Purge run time	Default 1 min* Options: off, 30 secs, 1, 2, 4 & 8 mins
Spout projection / total tap length	220mm / 250mm
Minimum flow pressure	1 bar (lower pressure station kits available)
Volume flow rate at 3 bar	5LPM (other flow rates available)
Adjustable run time	Yes* - Default: 2 secs Options: 2, 5, 10, 15, 20, 30 secs
Water connection	10mm Copper tails
Anti-vandal function	Yes
Lock out function	Default off* Options: OFF, 4, 6, 8 & 10 operations
Chlorination function	Yes* - Default 2 mins Options: 1, 2, 3, 4, 5, 10, 20 & 30 mins
Battery or mains station kit	Single battery: AT00-001 Single mains: AT00-002 Other options available
Working pressure	1-10 Bar (For Low / High pressure, Contact DELABIE-DVS.)
Max working temperature	60°C
Fixing	¾" BSP
Fixing length	Up to 30mm with flange nut