



#### AT02-025

AQUARIUS WM straight polished with pex hose

The Aquarius range incorporate simple and modern design, with the latest electronic functionality. Sensor operated for maximum hygiene and efficiency. 5 litres per minute integrated flowcontrol. (Standard 5LPM, Other flow rates available) Automatic purge function, Sensor range adjustment, Wave on/wave off function,

Anti Vandal and Lock Out functions, Chlorination function. Single mixed feed connection by PEX lined hose (15mm connection). External TMV required. Polished finish. Requires a Station kit to operate. Station kits available in Single Station Battery or Mains Single Station, 2 Station or 3 Station for multiple connections. Refer to Station kit Data sheets.

#### Technical data

Material	316 Stainless Steel
Gross weight	1.3kg
Type of operation	No touch sensor
Type of mounting	Wall mounted
Surface finish	Polished
Type of mixing	Additional TMV may be required
Automatic purge	Yes* - Default: OFF Options: 3. 6. 12. 24. 36 & 48 hours Additioonal feature (delete lines if not needed)
Purge run time	Default 1min* / Options: OFF, 30 secs, 1, 2, 4 & 8 mins
Spout projection / Total tap length	220mm / 250mm
Minimum flow pressure	1.00 bar (Lower pressure station kits available)
Volume flow rate at 3 bar	5LPM (Other flow rates available)
Adjustable run time	Yes* - Default: 2 secs / Options: 2, 5, 10, 15, 20 & 30 secs
Water connection	15mm PEX hose
Anti-Vandal function	Yes
Lock out function	Default OFF*/ Options: OFF, 4, 6, 8 & 10 operations
Chlorination function	Yes* - Default: 2 mins/ Options: 1, 2, 3, 4, 5, 10, 20 & 30 mins
Battery or mains station kit	Single Battery: AT00-001 Single Mains: AT00-002 - Other options available. Contact KWC DVS.
Working pressure	1-10 Bar (For Low / High pressure, Contact KWC DVS.)
Max working temperature	60°C
Fixing	¾" BSP
Fixing length	Up to 30mm with flange nut