TAP CONTROL SYSTEM KIT

2 Station - Tactile


AT07-013




| TECHNICAL DATA | |
|-----------------------|---|
| Material | ABS |
| Gross weight | 0.70 kg |
| Type of mounting | Wall mounted |
| Power source | Mains |
| Voltage | 230V a.c. |
| Sensor voltage | 5V DC |
| Valve voltage | 12V DC |
| Valve power | 3W normally closed |
| Control inputs | Sensor 1, sensor 2 |
| Control outputs | Valve 1, valve 2 |
| Control configuration | Controls valves for 1 or 2 spouts, or hot and |
| | cold valves for single spout |
| Operation type | Wave-on or tactile sensor (sold separately) |
| IP rating | 54 |
| Current | 0.055A |
| Frequency | 50Hz |
| Settings | |
| Adjustable timing | 6 - 20 secs (Default 6 secs) |
| Purge facility | Yes (ON / OFF) Default OFF |
| Operations lock out | Yes (ON / OFF) |
| Kit Contents | |
| AT07-001 | Tap control system for 1 or 2 taps |
| AC17-009 | Plastic valve 12v DC - 12.7mm orifice |
| AC02-046 | Tactile switch with 50mmø stainless steel bezel |
| | & blue insert |
| AC02-047 | Tactile switch with 50mmø stainless steel bezel |

& red insert







ALL DIMENSIONS IN MM

2017-03-10, Dart Valley Systems

