

WC FLUSHVALVE STANDARD KIT

WC FLUSHVAVE

The DVS WC Flushvlave is electronically operated, delivering a measured volume of water upon activation. Flush duration can be adjusted to suit specific requirements.

Our safe and reliable flushvlave system contains few moving parts, requires no maintenance and is easily installed in existing and new cisterns using industry standard fittings.

DVS WC flushvalves can achieve a typical 30% saving on water.

FEATURES

- 4.5 litre flush
- Adjustable for optimum flush
- Built-in overflow pipe
- Operated using DVS hygienic no-touch sensor
- Typical 30% savings on water costs



<< WC01-023
2" base fitting

WC FLUSHVALVE CONTROL BOX & STANDARD SENSOR

A simple wave of the hand past the DVS sensor activates the electronic flushvalve via the WC Flushvlave Control System, in return delivering the optimum flush.

The control box enables adjustment of flush duration, auto purge facility and lock-out option for high security applications.

Delivering an accurate measured flush every operation can help achieve significant water savings.

FEATURES

- Hygienic no-touch sensor operation
- Adjustable flush duration
- Auto purge and lock-out options
- Eliminates flush handle maintenance
- Wave-on or tactile control options available
- 38mm or 50mm chrome sensor bezels available and optional chrome backplate (pictured)
- Reliable and high performance



To view more products from the DVS WC Flushing range, please visit...
www.dartvalley.co.uk