


KWC

Self closing shower





F3SV2001

Self closing shower

F3S self-closing bib tap DN 15 as wall fitting for wall mounting for shower facilities. Self-closing functional part, hydroulically controlled, piston-free design, self-closing, stepless adjustment of flow duration. For connection to pre-mixed hot water or cold water. Housing including changeable valve seat, with outlet on top, G 3/4 B, for installation of bent outlet or surface-mounted shower pipe, high-polished chromium-plated brass.

Technical data

| Technical data | |
|-------------------------------------|------------------------|
| Tailor made | No |
| Type of operation | Manual operation |
| Diameter nominal | DN 15 |
| Inlet size | G 1/2 B |
| Material fitting | Brass |
| Type of mixing | No mixing |
| Sound insulation | No |
| Surface finish fitting | Chromium-plated brass |
| Calculation flow rate cold water | 0.15 litre per second |
| Minimum flow pressure | 1 bar |
| Volume flow rate at 3 bar | 0.2 litre per second |
| Adjustable flow time | Yes |
| Functional principle | Hydraulic self-closing |
| Protective shutdown | No |
| Thermal disinfection | No |
| Additional connections | No |
| Circulation | No |
| Connection with pay water dispenser | Not possible |
| Shower pipe draining | No |
| Type of shower | Wall fitting |
| Position of water connection | From backside |
| Maximum flow time | 35 seconds |
| Minimum flow time | 5 seonds |



KWC

Self closing shower

Optional accessories





Optional accessories

AQUA757 AQUAJET-Slimline shower head

Optional accessories

SHAC0008 AQUAJET-Comfort shower head