

# TAP: F1062

F1062 | 2000100425

PRODUCT GROUP : **Taps** | ARTICLE GROUP : **F1062** | ARTICLE FAMILY : **Manual taps**



Manufactured from chromium plated brass, both are suited for those locations where there is a need for a thorough rinsing of utensils and crockery in dishwashing areas. F1061 monobloc spray is designed to be fitted into a single taphole behind the bowl whereas the F1062 deck mixer spray fits into taphole centres of 180mm. Both models are supplied complete with spray valve and 150mm wall bracket. Suitable for temperatures up to 130°F.

WRAS Approved

Deck pattern mixer overhead spray

## TECHNICAL DATA

|                                  |                       |
|----------------------------------|-----------------------|
| calculation flow rate cold water | 0.20 liter per second |
| calculation flow rate hot water  | 0.20 liter per second |
| gross weight                     | 0.00 kg               |
| diameter nominal                 | DN 10                 |
| minimum flow pressure            | 0.20 bar              |
| type of mixing                   | with mixer            |
| overall depth                    | 185.00 mm             |
| overall height                   | 1,016.00 mm           |
| overall width                    | 370.00 mm             |
| sound insulation                 | no                    |
| spout projection                 | 381.00 mm             |
| surface material                 | chrome                |
| type of fitting                  | lever mixer           |
| volume flow rate at 3 bar        | 0.20 liter per second |
| net weight                       | 0.00 kg               |