
MODEL RANGE: F5 | F5ST2026 | 210.0595.592

Showers | Self closing showers





F5S Therm shower panel made of mineral material for wall mounting with DN 15 self-closing thermostatic mixer and connecting nozzles for the shower head. Hydraulically controlled, for connection to hot water and cold water. Shower valve with integrated FRAMIC self-closing cartridge, thermostat and pre-assembled hygiene unit including sensor with control electronics to perform automatic water hygiene flushing, program-controlled thermal disinfection (additional bypass solenoid-operated flush valve cartridge required) and storage of statistical data. FRAMIC self-closing cartridge, low maintenance and stagnation free, with ceramic disc technology, self closing, flow pressure independent due to the medium-independent design. Stepless adjustment of flow duration. Thermostat with metal handle, an adjustable and turn-proof temperature stop and an option for manual thermal disinfection. All-metal construction, visible parts high-polished or chrome-plated. Connecting nozzles for the required additional DN 15 Franke shower head with pre-fitted flow regulator 9.0 I/min. Housing with raised function surface and seamless moulded shower gel shelf made of MIRANIT resin-bonded mineral material with pore-free smooth surface (temperature-resistant up to 80 °C), Alpine white colour. Connecting hoses with lockable water volume control with backflow preventer and strainer. Activated water hygiene flushing at fixed intervals of 24 hours. With option for parameterization and communication via the optional bidirectional remote control. Optional hygiene unit for battery operation with 6 V lithium battery (CR-P2) per fitting or separate power supply via plug-in power supply unit 6.75 V/12 V DC.

Dimensions of housing 235 x 1160 x 100 mm (W x H x D)

Technical data

Battery compartment including battery or plug-in power supply unit with extension cable to be ordered separately.

recillical data	
Overall depth	100.00 mm
Overall height	1,160.00 mm
Overall width	235.00 mm
Type of mounting	Wall mounting
Type of operation	Manual operation
Diameter nominal	DN 15
Inlet size	G-1-2-A
Material casing	Mineral material
Material fitting	Brass
Type of mixing	Thermostat
Sound insulation	No
Surface finish fitting	Chromed
Minimum flow pressure	1.50 bar
Volume flow rate at 3 bar	0.15 liter per second
Adjustable flow time	Yes
Functional principle	Hydraulic self-closing
Protective shutdown	No
Thermal disinfection	Prepared for automatic thermal
	disinfection
Default automatic hygiene flushing	Fixed interval 24 hours
Power supply connection	6-12-VDC
Type of sensor	Opto-electronic sensor
PownkerWateo โดยรายาการ de marinfo.int@franke.co	om www.fognkerckendel 2020-07-30
Additional connections	No
Circulation	No
Connection with pay water dispenser	Not possible
Shower pipe draining	No














MODEL RANGE: F5 | F5ST2026 | 210.0595.592

Showers | Self closing showers

Accessory Mandatory





2030054255 SHAS0011



AQUAJET-Comfort shower head for F5 shower panels

2030054254 SHAC0011



MÜNCHEN shower head for F5 shower panels

2030054793 SHMU0011



Battery compartment

2000109466

ZAQCT0003



Extension cable 5 m

2030043814



Accessory Optional

Power supply unit

2030039477

ACEX9001



Flow controller 12,0 I/min

2000104783 ESHHE0002



Bidirectional remote control for electronical fittings F3 and F5

2030036654



2-button remote control for fittings F3 and F5

2030036849



Housing extension for F5 shower panels made of MIRANIT

2030057071

ACXX2016



MODEL RANGE: F5 | F5ST2026 | 210.0595.592


Showers | Self closing showers

Accessory Optional



Housing extension for F5 shower panels made of MIRANIT

2030057072 ACXX2017



Housing extension for F5 shower panels made of MIRANIT

2030057073 ACXX2018



Housing extension for F5 shower panels made of MIRANIT

2030057075 ACXX2019



Housing extension for F5 shower panels made of MIRANIT

2030057076 ACXX2020



Connection adapter

2000101441 AQRM928



Spare Parts



Flow controller 9,0 I/min

2000104782 ESHHE0001



Cover

2030031443 ESHOW0059



Temperature handle

2030047082 ASXT9003



Temperature stop

2030003296

EAQLT0003

FRAMIC Self-closing cartridge

2030046145

ASSX9001

MODEL RANGE: F5 | F5ST2026 | 2030054253

Showers | Self closing showers

Rosette

2030048765

ASET2006

| Push cap | Guide ring | Safety ring | 2030049357 | ASSX9004 | ASST2001 | ASSX9002 | ASSX9003 |

Solenoid valve cartridge

2030003033 EAQFU0001



Disassembly tool

2030047203

ACXX9003