

Directory Search Results

WRAS Approval Number: 2009303

Approved Product

Range of two hole, singleoutlet (swivel) combination tap assemblies (chromium plated brass). Incorporating non rising spindle headworks with various operating members. The spout outlets incorporate a plastic flow straightener. Products are supplied with plastic backnuts, model DCM SPEC105 is supplied with metal backnuts Maximum working pressure 10.0 bar. Maximum operating temperature 60°C.

- **Section:** 0550 Combination Tap Assemblies (?section=0550)
- **Section Subtitle:** Two hole, metal, single outlet, swivel. Taps used in high risk installations, such as kitchen sinks, are considered to be a fluid category 5 risk. Backflow protection is usually provided in the form of an AUK3 tap gap. Where an AUK3 tap gap cannot be maintained, for example where the tap gap is compromised as a result of:-
 - the tap being lowered in any way;
 - adjustment to the spout which reduces the distance between the tap outlet and spillover level of the sink;
 - or the operation of a pull out hose attachment; alternative fluid category 5 backflow protection is required.
- **WRAS Approval Number:** 2009303
- **Expiry date:** 30/09/2025
- **Size:** ½" BSP (M)
- **Marking:** DTC34 (brand of Methven) on rear of body.
- **Installation Requirements R001**
(/approvals/resources/fittings/installation_requirements/irn_r001)R006
(/approvals/resources/fittings/installation_requirements/irn_r006)R010
(/approvals/resources/fittings/installation_requirements/irn_r010)
- **Model**
187X
DCM105
VW DCM105
208.0574.212
DCM SPEC105
MILAN 105
- **Factor:** Methven UK Ltd View All Listings by this Company (?company=16309)