

Directory Search Results

WRAS Approval Number: 1912311

Approved Product

Range of two hole, single outlet (swivel) combination tap assemblies (chromium plated brass), incorporating quarter turn ceramic disc headworks with single lever operating members. The spout outlet incorporates a plastic flow straightener. The product is supplied with plastic backnuts. Maximum working pressure 10.0 bar. Maximum operating temperature 65°C

- **Section:** 0550 Combination Tap Assemblies (?section=0550)
- **Section Subtitle:** Two hole, metal, single outlet, swivel. Taps used in high risk installations, such as kitchen sinks, are considered to be a fluid category 5 risk. Backflow protection is usually provided in the form of an AUK3 tap gap. Where an AUK3 tap gap cannot be maintained, for example where the tap gap is compromised as a result of:-
 - the tap being lowered in any way;
 - adjustment to the spout which reduces the distance between the tap outlet and spillover level of the sink;
 - or the operation of a pull out hose attachment;alternative fluid category 5 backflow protection is required.
- **WRAS Approval Number:** 1912311
- **Expiry date:** 31/12/2024
- **Size:** ½" BSP (M)
- **Marking:** DTC34 (brand name of Methven) on rear of body.
- **Installation Requirements** R001 (/approvals/resources/fittings/installation_requirements/irn_r001)R006 (/approvals/resources/fittings/installation_requirements/irn_r006)R010 (/approvals/resources/fittings/installation_requirements/irn_r010)
- **Model**
DLT105,
VW DLT105,
DLT SPEC105,
208.0574.213,
320890,
DLV105,
NLT105,
60177101.
- **Factor:** Methven UK Ltd View All Listings by this Company (?company=16309)