
KWC DVS


KWC

CENTINEL 1800mm urinal with exposed sparge pipe

Model line: URINALS | CEN180E







CEN180E

1800mm centinel urinal with exposed sparge pipe

Manufactured from 1.2mm thick grade 1.4301 (304) stainless steel with a satin polish finish. Designed with the waste outlet positioned centrally within the urinal. Supplied complete with a 2" Domed waste, exposed sparge pipes, sparge pipe cover, interconnecting pipework, 13.5 litre cistern and downpipe. The recommended height for fixing the cisterns is 750 - 950mm, from the underside of the cistern to the top return of the urinal. All urinals are screw fixed to the wall through fixing holes in the top flange together with separate wall mounted brackets which support the base of the unit.

Technical data

| Material | | |
|--------------------|--|--|
| Gross weight | | |
| Overall dimensions | | |
| Material thickness | | |
| Surface finish | | |
| Type of flushing | | |
| Waste size | | |
| Water inlet | | |
| Water outlet | | |
| Cistern | | |
| | | |

| Stainless steel | |
|---------------------------------|--|
| 23kg | |
| 1800 x 300 x 555 mm (w x h x d) | |
| 1.2mm | |
| Satin | |
| Water flushed | |
| 50mm | |
| Exposed | |
| Exposed | |
| 13.5L Cistern F3049 | |