


### **KWC**

# F3E electronic pillar tap with battery compartment

### Modell-Linie: F3 | F3EV1001

Taps | Electronic taps





#### KWC-No.

#### 2030033385

F3E pillar tap DN 15 for sanitary facilities, opto-electronically controlled. For connection to pre-mixed hot or cold water via hose and strainer. Control electronics, solenoid valve cartridge and sensor in all-metal housing, high-polished chromium-plated brass. Aerator with integrated flow regulator 6.0 l/min. Activated water hygiene

#### volume flow rate at 3 bar

0.1 l/s

flushing 24 hours after last activation, safety switch-off with continuous reflection and saving of statistical data. With option for parameterization and communication via optional, bidirectional remote control. With battery compartment including 6 V lithium battery (CR-P2) for installation under the washbasin.

#### Technical Data

with backflow preventer
calculation flow rate cold wat
compatible A3000 open
default automatic hygiene flus
depressurised
with filter
functional principle
hygiene flushing
diameter nominal
inlet size
Locking mechanism
material fitting
minimum flow pressure
type of mixing
number of batteries
Parameterization
Pop-up waste set
power supply connection
position of power connection
power consumption
Type of power supply
protective system IP
with rosettes/cover plate
protective shutdown
· · · · · · · · · · · · · · · · · · ·

10
0.1 l/s
00
24h after the last activity
10
res
electronic self-closing
res
DN 15
G 3/8
op section, non-ceramic
prass
bar
10
emote control
10
Battery 6 V
rom bottom
5 Voltampere
Battery
P59K
10









# **KWC**

# F3E electronic pillar tap with battery compartment

### Modell-Linie: F3 | F3EV1001

Taps | Electronic taps

sound insulation	no
Spout	fixed
spout projection	100 mm
surface finish fitting	chromed
surface treatment fitting	polished
tailor made	no
temperature limit	no
thermal disinfection	no
with transformer/power supply	no
type of batteries	CR-P2 Lithium battery 6V
type of mounting	tap hole
type of operation	sensor operation
type of sensor	opto-electronic sensor
type of tap	pillartap
volume flow rate at 3 bar	0.1 l/s
water connection	hose (gland nut)
Accent colour	none
Basic colour	chrome-look (glossy)

### **Optional Accessories**









Bidirectional remote control for electronical fittings F3 and F5

**2030036654** ACEX9005 2-button remote control for fittings F3 and F5

**2030036849** ACEX9004 Aerator

**2000101160** ZAQUA087

PURETHERM under-table thermostat

**2030012758** PURE0031

#### **Spare Parts**











## **KWC**

F3E electronic pillar tap with battery compartment

# **Modell-Linie: F3 | F3EV1001** Taps | Electronic taps

Solenoid valve cartridge	Battery compartment	Plug-in power supply unit	In-wall power supply
<b>2030003033</b>	<b>2000109466</b>	<b>2030039823</b>	<b>2030039825</b>
EAQFU0001	ZAQCT0003	ACEX9002	ACEX9003